

Drilling

CP7300

2,800 RPM



COMPACT & COMFORT

FEATURES

- 1/4" (6 mm) compact drill
- Ergonomic grip and lightweight, only 1.35 lbs (0.61 kg)
- Teasing throttle
- Durable gearbox for low wear and long life
- Adjustable exhaust

CP7300R

Similar features as CP7300 with reversible function (2,700 rpm)

BENEFITS

- Drills for General Maintenance, efficient and great for tight areas with its size
- Good precision to allow for very slow start-up and control throughout the drilling process
- Excellent for drilling, honing, reaming, and hole sawing



2,400 RPM

CP785



DURABILITY AND SMOOTH OPERATION

FEATURES

- 3/8" (10 mm) pistol drill
- Powerful energy efficient motor resists stalls
- Handle exhaust

BENEFITS

- Drills for Industrial Maintenance with smooth operation and extended tool life
- Ideal tool for all types of maintenance work



See accessories on page 114

CP9790

2,000 RPM



REVERSIBLE, PRODUCTIVITY

FEATURES

- 3/8" (10 mm) reversible pistol drill
- Powerful motor
- Industrial quality Jacobs chuck
- Ergonomic grip
- Handle exhaust

CP9792

Same features as CP9790 with keyless chuck

BENEFITS

- Drills for General Maintenance with productivity
- Maximize operator comfort
- Power suitable for many applications
- Ideal tool for drilling and screw driving



2,600 RPM

CP789R-26



REVERSIBLE, HIGH POWER & DURABILITY

FEATURES

- 3/8" (10 mm) reversible pistol drill
- Powerful with 0.5 hp (370 W) motor
- Teasing throttle
- Industrial quality Jacobs chuck
- Durable gearbox
- Ergonomic grip

CP789R-42

Similar features as CP789R-26 with 4200 rpm

BENEFITS

- Drills for Industrial Maintenance, great for operators' productivity, durability & comfort
- Great tool for honing and heavy drilling

MODEL	PART NUMBER	FREE SPEED		POWER		CHUCK CAPACITY		STALL TORQUE		NET WEIGHT		LENGTH		AIR CONS. @LOAD		VIBRATION LEVEL ISO 29927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
		rpm	hp	W	in.	mm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744-dB(A)	in.		
CP785	T022698	2,400	0.5	380	3/8	10	3.1	4.2	2.3	1.0	7.0	178	16.5	8	<2.5	-	90	101	1/4	
CP789R-26	T025180	2,600	0.5	375	3/8	10	3.1	4.2	2.5	1.1	7.0	178	30.0	14	<2.5	-	95	106	1/4	
CP789R-42	T025198	4,200	0.5	375	3/8	10	1.9	2.5	2.5	1.1	7.0	178	30.0	14	<2.5	-	96	107	1/4	
CP7300	894 107 3000	2,800	0.3	230	1/4	6	2.4	3.3	1.4	0.6	5.0	127	16.4	8	<2.5	-	86	97	1/4	
CP7300R	894 107 3001	2,700	0.3	200	1/4	6	2.2	3.0	1.4	0.6	5.0	127	16.4	8	<2.5	-	87	98	1/4	
CP9790	615 194 9790	2,000	0.4	270	3/8	10	3.5	4.8	3.0	1.4	6.5	165	24.0	11	<2.5	-	89	100	1/4	
CP9792	615 194 9792	2,000	0.4	270	3/8	10	3.5	4.8	2.6	1.2	8.5	216	24.0	11	<2.5	-	90	101	1/4	

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com