

# Bolting

## CP7759Q



COMFORT & POWER



### FEATURES

- 1/2" composite & carbon fiber impact wrench
- Rugged technology with carbon fiber inlay
- Lightweight with a magnesium clutch housing
- S2S easy forward reverse: Side to Side patented technology
- 780 ft.lbs (1,054 Nm) of maximum torque in reverse
- Universal & durable twin hammer mechanism
- Full teasing ergonomically developed trigger
- Ergonomic handle in composite material
- Integrated muffler for low noise
- Flexible 360° swivel air inlet

### BENEFITS

- New technology maximizing comfort and power for General Maintenance
- Maximize operator comfort thanks to Unique CP Handle design
- Great power in a lightweight package
- Side-to-side: the Most convenient reverse technology in the market



See accessories on pages 30 to 34

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @ LOAD		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
					ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K			
CP7748	894 107 7480	1/2"	1,200	8,200	75-580	102-786	920	1,250	4.4	2.0	7.6	195	21.0	10.0	7.4	2.2	93	104	1/4
CP7759Q	894 107 7518	1/2"	1,200	8,000	75-460	100-630	780	1,054	3.7	1.7	7.4	187	23.0	11.0	8.1	1.7	93	104	1/4

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

## CP7748



EXTREME TORQUE & POWER



### FEATURES

- 1/2" composite impact wrench with ring retainer
- 920 ft.lbs (1,250 Nm) of maximum torque in reverse
- Aluminum clutch & rear housings
- Thermo-plastic rubber injected in housing for a durable and comfortable grip
- Universal & durable twin hammer mechanism
- Full teasing ergonomically developed trigger
- 360° swivel air inlet

### BENEFITS

- General Maintenance
- Maximize work efficiency thanks to extreme torque
- Insulated and comfortable grip with rubber injected composite housing

