

Grinding

<0.54 hp (400W) Die Grinders

CP9105Q-B



QUIET & EFFICIENT

FEATURES

- 0.32 hp (240 W) motor
- 28,000 rpm free speed
- Low noise level: only 81 dB(A)
- Built-in air regulator
- Rubber overmould grip
- Rear exhaust
- Swivel air inlet
- Includes 1/4" and 6 mm collets

BENEFITS

- General Maintenance Applications die grinder
- High operator comfort
- Power and performance
- Ideal for limited space applications

CP9106Q-B

Similar features as CP9105Q-B with 22,000 rpm and 90° angle head



CP9108Q-B

Similar features as CP9105Q-B 22,000 rpm and 120° angle head



CP9110Q-B

Similar features as CP9105Q-B 25,000 rpm and with extended shaft



CP9111Q-B

22,000 RPM



CP9112Q-B

Similar features as CP9111Q-B with extended shaft

POWERFUL & QUIET

FEATURES

- 0.47 hp (350 W) motor
- 22,000 rpm free speed
- Low noise level: only 80 dB(A)
- Built-in air regulator
- Rubber overmould grip
- Rear exhaust
- Swivel air inlet
- Includes 1/4" and 6 mm collets

BENEFITS

- General Maintenance Applications die grinder
- High operator comfort
- Power and performance
- Ideal for limited space applications



See accessories on pages 60 to 63

CP860



24,000 RPM



CP860E

Same features as CP860 with 6 mm collet

CP860ES

Same features as CP860 with 6" extended shaft

CP860ESE

Same features as CP860E with 6" extended shaft and 6 mm collet

GREAT DURABILITY

FEATURES

- 1/4" collet
- Rugged and energy efficient 0.54 hp (400 W) motor
- Adjustable speed regulator
- Lock-off throttle
- Square handle design for greater comfort

BENEFITS

- General Maintenance Applications die grinder
- Productivity and control
- Excellent for cleaning tires, moldings, porting, relieving engines, and general high-speed polishing and grinding

MODEL	PART NUMBER	FREE SPEED		POWER		COLLET CAPACITY		AIR CONS. AT FREE SPEED		AIR CONS. @LOAD		NET WEIGHT		LENGTH		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
		rpm		hp	W	in.	mm	cfm	l/s	cfm	l/s	lb	kg	in.	mm	a	k			
CP860	T019704	24,000	0.54	400	1/4	-	21.0	9.9	21.0	9.9	1.3	0.6	5.8	146	3.7	1.6	93	104	1/4"	
CP860E	T021136	24,000	0.54	400	-	6	21.0	9.9	21.0	9.9	1.3	0.6	5.8	146	3.7	1.6	93	104	1/4"	
CP860ES	T023193	24,000	0.54	400	1/4	-	23.0	10.8	23.1	10.9	2.1	1.0	11.8	294	3.7	1.5	93	104	1/4"	
CP860ESE	T023354	24,000	0.54	400	-	6	23.0	10.8	23.1	10.9	2.1	1.0	11.8	294	3.7	1.5	93	104	1/4"	
CP9105Q-B	615 195 2105	28,000	0.3	240	1/4	6	19.7	9.3	8.7	4.1	0.8	0.4	6.4	163	3.6	2.0	80	91	1/4"	
CP9106Q-B	615 195 2106	22,000	0.3	240	1/4	6	19.3	9.1	8.7	4.1	1.5	0.7	4.7	120	5.1	2.6	80	91	1/4"	
CP9108Q-B	615 195 2108	22,000	0.3	240	1/4	6	19.3	9.1	8.7	4.1	1.1	0.5	7.9	200	5.1	1.6	80	91	1/4"	
CP9110Q-B	615 195 2110	25,000	0.3	240	1/4	6	18.3	8.6	8.7	4.1	1.5	0.7	10.0	256	4.9	2.5	80	91	1/4"	
CP9111Q-B	615 195 2111	22,000	0.47	350	1/4	6	23.1	10.9	8.7	4.1	1.5	0.7	6.7	170	3.7	1.6	80	91	1/4"	
CP9112Q-B	615 195 2112	22,000	0.47	350	1/4	6	25.0	11.8	8.7	4.1	2.9	1.3	13.0	330	2.7	1.2	80	91	1/4"	

All models: Hose int. 3/8" (9.5mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.