

2.8 hp (2,100W) Sanders

CP3850-65ABVE



UNIQUE FEATURES
Premium Tool

SUPER INDUSTRIAL

CP3850-60AB SUPERLATIVE PERFORMANCE & ERGONOMICS

Similar features as CP3850-65ABVE with 6,000 rpm free speed and without autobalancer

For ANSI markets

FEATURES

- 9" (230 mm) pad capacity
- 2.8 hp (2,100 W) high performance governed motor
- 6,500 rpm free speed
- Low profile angle head
- Superior durability bevel gear
- Curved handle housing
- Double action safety lever
- Integrated silencer
- Orientable exhaust
- Spindle lock button
- Auto balancer
- Vibration damping multi-position side handle
- **CE certification / not for North American Market**

BENEFITS

- Industrial Maintenance and Production angle sander
- Highest durability in demanding applications up to 2,000 hours maintenance intervals
- Superior torque for maximal productivity
- Superior ergonomics

See all CP3850 Unique Features on page 72



CP3850-65ABVE

CP3850-85ABVE

SUPERLATIVE PERFORMANCE & ERGONOMICS

UNIQUE FEATURES
Premium Tool

FEATURES

- 7" (180 mm) pad capacity
- 2.8 hp (2,100 W) high performance governed motor
- 8,500 rpm free speed
- Low profile angle head
- Superior durability bevel gear
- Curved handle housing
- Double action safety lever
- Integrated silencer
- Orientable exhaust
- Spindle lock button
- Auto balancer
- Vibration damping multi-position side handle
- **CE certification / not for North American Market**

BENEFITS

- Industrial Maintenance and Production angle sander
- Highest durability in demanding applications up to 2,000 hours maintenance intervals
- Superior torque for maximal productivity
- Superior ergonomics



SUPER INDUSTRIAL

CP3850-85ABVE

CP3850-77AB

Similar features as CP3850-85ABVE with 7,700 rpm free speed and without autobalancer for ANSI markets



See accessories on pages 102 to 105

MODEL	PART NUMBER	FREE SPEED	POWER		PAD CAPACITY		SPINDLE TRHEAD	AIR CONS. AT FREE SPEED		AIR CONS. @LOAD		NET WEIGHT		LENGTH		VIBRATION LEVEL ISO 28927 (M/S2)		SOUND PRESS.	SOUND POWER	AIR INLET
		rpm	hp	W	in.	mm	in.	cfm	l/s	cfm	l/s	lb	kg	in.	mm	a	k	ISO 15744 - dB(A)		
ANSI MODELS																				
CP3850-60AB	615 170 5000	6,000	2.8	2,100	9	230	5/8-11	38	18	80.0	38.0	5.1	2.3	13	340	<2.5		86	97	1/2"
CP3850-77AB	615 170 4990	7,700	2.8	2,100	7	180	5/8-11	33	16	69.0	32.0	4.1	2.3	13	340	3.6	0.8	84	95	1/2"
CE MODELS - NOT FOR NA																				
CP3850-65ABVE	615 170 4980	6,500	2.8	2,100	9	230	5/8-11	44	21	80.0	38.0	5.1	2.3	13	340	<2.5		89	100	1/2"
CP3850-85ABVE	615 170 4970	8,500	2.8	2,100	7	180	5/8-11	36	17	77.0	36.0	5.1	2.3	13	340	<2.5		87	98	1/2"

All models: Hose int. 5/8" (15mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.